

**DEVICE AND METHOD FOR HANDLING A BOAT SUNDECK**

**Priority of Invention**

5           This application claims priority of invention under 35 U.S.C. §119(e) from U.S. Provisional application number 60/257,665, filed December 21, 2000, the disclosure of which is incorporated by reference herein.

**Field of the Invention**

10           The present invention relates generally to devices and methods for assembling products such as boats. More particularly, the present invention relates devices and methods for handling boat sundecks.

**Background of the Invention**

15           Conventional boat manufacturing processes are typically quite labor intensive and involve a significant amount of manual lifting and positioning of component parts. What are needed are methods and devices for improving manufacturing efficiency on a boat assembly line.

**Summary of the Invention**

20           One aspect of the present invention relates to a device for handling a boat sundeck. The device includes a platform having first and second ends. A clamp structure is connected to the first end of the platform such that the clamp structure can be used to hold and move the sundeck of a boat. In addition, control modules are connected to the second end of the platform to aid in manipulation of the sundeck by the device. A lift connection location is positioned between the first and second ends of the platform and allows the device to be connected to an articulated boom.

25           Another aspect of the present invention relates to a method for mounting a sundeck to a boat. The method includes providing a clamp structure including a moveable clamping member and a fixed clamping member. The method also includes

maneuvering the clamp structure such that the moveable and fixed clamping members are located on either side of one end of a boat sundeck and then closing the clamp structure such that the device clamps the sundeck. The method further includes lifting the sundeck with a boom and lift assembly connected to the clamp structure and

5 connecting the sundeck to the back of the boat (e.g., near the transom and over the engine) while the boom and lift assembly holds the clamped sundeck in the desired position.

A variety of advantages of the invention will be set forth in part in the description that follows, and in part will be apparent from the description, or may be

10 learned by practicing the invention. It is to be understood that both the foregoing general description and the following detailed description are explanatory only and are not restrictive of the invention as claimed.

### **Brief Description of the Drawings**

The accompanying drawings, which are incorporated in and constitute a part of

15 the specification, illustrate several aspects of the invention and together with the description, serve to explain the principles of the invention. A brief description of the drawings is as follows:

Figure 1 is a side view of an articulated arm/boom suitable for use with an attachment constructed in accordance with the principles of the present invention;

20 Figure 2 is a perspective view of the frame of an articulated boom attachment constructed in accordance with the principles of the present invention;

Figure 3 is a side view of the frame of the attachment of Figure 2;

Figure 4 is a back perspective view of the attachment;

Figure 5 is a front perspective view of the attachment; and

25 Figure 6 is a perspective view of the attachment clamped onto a sundeck for a boat.

### Detailed Description

With reference now to the various drawings in which identical elements are numbered identically throughout, a description of various exemplary aspects of the present invention will now be provided.

5           Figure 1 shows an articulated boom 20 (i.e., a jib or crane) suitable for use with a sundeck handling attachment constructed in accordance with the principles of the present invention. The articulated boom 20 includes a main post 22 having a base piece 24 and an upper extension 26. The upper extension 26 is free to pivot about a vertical axis 28 that extends longitudinally through the main post 22. A first arm 30 projects  
10           outwardly from the upper extension 26 in a cantilevered fashion. The far end of the first arm 30 is connected to a second arm 32 by a pivot mount 34. The pivot mount 34 allows the second arm 32 to pivot relative to the first arm 30 about a vertical axis 36. A lift 37 (i.e., a winch-like structure) for raising and lowering a flexible member 39 (e.g., a cable, rope, chain, etc.) is mounted on the second arm 32. It will be appreciated that  
15           articulated booms as described above are conventionally known in the art. For example, similar booms are manufactured and sold by GCI Company of Garfield, Minnesota. Additionally, lifts as described above are also known in the art. For example, a preferred lift is sold under the name Bal-Trol by Tri-Motion Industries of Tampa, Florida.

20           A sundeck handling attachment 42 constructed in accordance with the principles of the present invention is preferably connected to the lower end of the flexible member 39. It will be understood that the phrase "connected to" includes direct connections as well as connections made by intermediate pieces or structures. Figures 4-6 show the entire sundeck handling attachment 42, while Figures 2 and 3 show only a frame 43 of  
25           the handling attachment 42.

Referring to Figures 2 and 3, the frame 43 includes a platform 45 with first and second ends 48 and 49. A lift connection location 60 (e.g., an eye, loop, hook, flange, opening, etc.) is positioned on the platform 45 between the first end 48 and second end 49. The frame 43 further includes a clamp structure 62 with a cylinder mount 75, spacer  
30           85, and fixed clamping member 95. A first end 78 of the cylinder mount 75 is

connected to the first end 48 of the platform such that the two structures run perpendicular to one another. The cylinder mount defines a piston hole 76. A second end 79 of the cylinder mount 75 is connected to a first end 88 of the spacer 85 such that the cylinder mount 75 and spacer 85 are perpendicular to one another. Finally, a second  
5 end 89 of spacer 85 is connected to the fixed clamping member 95 such that the two structures run perpendicular to one another.

Referring now to Figures 4 and 5, an air cylinder 105 is connected to the back of cylinder mount 75 and positioned such that piston 106 (shown in Figure 6) of air cylinder 105 extends through piston hole 76 of cylinder mount 75. The end of the  
10 piston 106 is connected to a moveable clamping member 115 so that as the piston is actuated from a first retracted position to a second extended position, the moveable clamping member 115 is moved from a position close to the first end 88 of spacer 85 toward the second end 89 of spacer 85 so that the space between moveable clamping member 115 and fixed clamping member 95 is thereby reduced. When the piston 106 is  
15 actuated from a second position to a first position, the moveable clamping member 115 returns to its initial position, thereby increasing the space between moveable clamping member 115 and fixed clamping member 95.

The moveable clamping member 115 is generally rectangular and includes an outer edge 118 having a convex curvature. Upper corners 119 of moveable clamping member 115 are rounded. Preferably, the moveable clamping member 115 has a planar  
20 contact area 121 that is larger than an opposing contact area of the fixed clamping member 95. In one embodiment, the contact area of the moveable clamping member 115 is at least 50 percent larger than the contact area of the fixed clamping member 95.

Referring again to Figures 2 and 3, a control mounting bracket 125 is connected  
25 to the second end 49 of platform 45. The control mounting bracket 125 includes handle 128 connected to the control mounting bracket 125. The handle 128 can be used to manipulate the sundeck handling attachment 42 and attached sundeck during installation of the sundeck onto a boat. The control mounting bracket 125 includes a base plate 127 connected to the platform 45. The base plate 127 is preferably angled upwardly from  
30 the platform 45. The control mounting bracket also includes an upright leg 131 that

extends upwardly from the base plate 127. The base plate 127 and the leg 131 cooperate to give the bracket 125 an L-shaped configuration.

Referring to Figure 4, a clamp control module 135 and a lift control module 145 are mounted on the control mounting bracket 125. The clamp control module 135 includes a plurality of buttons 138. The buttons 138 can be used to control the air cylinder 105, actuating the piston 106 and thereby causing the clamp structure 62 to open or close. Preferably, the clamp control module 135 is mounted on the upright leg 131 of the bracket 125.

The lift control module 145 includes two or more levers 148 used to control the lift 37 of articulated boom 20. One lever 148 can be used to cause the sundeck handling attachment 42 to be raised to a higher elevation, and another lever 148 can be used to cause the sundeck handling attachment 42 to be lowered. The lift control module 145 is preferably mounted on the base plate 127.

Figure 6 illustrates the sundeck handling attachment 42 attached to a sundeck 205. To connect the sundeck 205 to a boat, the sundeck attachment 42 is manipulated so that the clamp structure 62 is positioned with the fixed clamping member 95 facing a first surface 208 and moveable clamping member 115 facing a second surface 209 of the sundeck 205. With the clamp structure 62 so positioned, the moveable clamping member 115 is clamped down on the surface 209 of the sundeck 205. The lift 37 is then used to lift the clamped sundeck 205 to a desired elevation, and the sundeck 205 manually moved to a location over the engine of the boat. As the sundeck 205 is moved, the arms of the articulated boom 20 pivot relative to one another to accommodate the movement. Once positioned over the engine, the sundeck is pivotally connected (e.g., by hinges and fasteners such as bolts) to the rear upper deck of the boat. During the connection process, the boom and lift assembly holds the clamped sundeck 205 at the desired position relative to the boat. After assembly, the engine can be accessed by pivoting the sundeck upwardly.

The above specification and examples provide a complete description of the manufacture and use of the composition of the invention. While a preferred use of the disclosed device is for handling the sundecks of boats, it will be appreciated that articles

and manufacturing components could also be handled with the device. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000